

香港商永道無線射頻標籤有限公司台灣分公司

Arizon RFID Technology(Hong Kong)Co.,Ltd.,Taiwan Branch.



Arizon RFID Technology, 100% owned by YFY Group, is a leading company to provide first-class manufacturing services of inlays /tags / tickets and cards for worldwide RFID industry. By 2012 Arizon has $\,$ produced and delivered more than 1 $\,$ billion inlays /tags and the number is 10 billion pcs by Apr. of 2019, all products conform to highest quality standards in HF and UHF technology for its valuable customers.

Arizon has established inlay/label monthly capacity up to 300 million pieces by 2018, and will continue its strong investments to further boost its monthly production capacity for satisfying the market's fast growing needs.

Overview

Operating Frequency

860MHz-960MHz

Integrated Circuit(IC)

Impinj Monza R6

Antenna Size

22x8mm

0.86x0.31inch

Protocol

EPC Class1 Gen2 ISO/IEC 18000-6C

Application Areas

Brand Protection Healthcare and medical Supply Chain Management

Electrical Characteristics

| Antenna | AZ-C6 | | | | |
|----------------|---------------------------------|--------|--------|-------------|--------|
| Base Material | PET | | | | |
| IC | Impinj Monza | R6 | R6-A | R6-P | S6-C |
| Memory | EPC: | 96Bits | 96Bits | 128(96)Bits | 96Bits |
| | User: | OBits | OBits | 32(64)Bits | 32Bits |
| | TID: | 48Bits | 48Bits | 48Bits | 48Bits |
| | Unique TID: | 48Bits | 48Bits | 48Bits | 48Bits |
| | Access Password: | OBits | 32Bits | 32Bits | 32Bits |
| | Kill Password: | OBits | 32Bits | 32Bits | 32Bits |
| IC Life | 100,000 Programming cycles | | | | |
| | 50 years data retention | | | | |
| Operating Mode | Passive | | | | |
| Frequency | 860 ~ 960MHz | | | | |
| Standards | ISO 9001:2008 | | | | |
| | ISO 14001:2004 | | | | |
| | OHSAS 18001:2007 | | | | |
| Frequency | ISO 9001:2008 ISO 14001:2004 | | | | |

www.arizonrfid.com

Copyright © 2019 Arizon RFID Technology Corporation All rights

reserved







香港商永道無線射頻標籤有限公司台灣分公司

Arizon RFID Technology(Hong Kong)Co.,Ltd.,Taiwan Branch.

Frequency Sweep







Test power: 4W EIRP

For countries that allow 2W ERP, please reduce the result by 11% $\,$

Radiation Patterns

Angular Sensitivity (dBm) ; Power step 0.1dB ; Angle step 10°





Angular Sensitivity
Inlay is rotated in the x,y axis, fixed in z axis
)Tag shown at 0° with respect to face of antenna(