

# 香港商永道無線射頻標籤有限公司台灣分公司 Arizon RFID Technology(Hong Kong)Co.,Ltd.,Taiwan Branch.



Arizon RFID Technology, 100% owned by YFY Group, is a leading company to provide first-class manufacturing services of inlays /tags /tickets and cards for worldwide RFID industry. By 2012 Arizon has produced and delivered more than 1 billion inlays /tags and the number is 10 billion pcs by Apr. of 2019, all products conform to highest quality standards in HF and UHF technology for its valuable customers.

Arizon has established inlay/label monthly capacity up to 300 million pieces by 2018, and will continue its strong investments to further boost its monthly production capacity for satisfying the market's fast growing needs.

#### Overview

## **Operating Frequency**

860MHz-960MHz

#### Integrated Circuit(IC)

Impinj Monza R6

#### Antenna Size

45x20mm

1.77x.0.78inch

#### **Protocol**

EPC Class1 Gen2 ISO/IEC 18000-6C

#### **Application Areas**

**Brand Protection** 

Industry/Retail

Supply Chain Management

# **Electrical Characteristics**

Antenna	AZ-M6HB				
Base Material	PET				
IC	Impinj Monza	R6	R6-A	R6-P	S6-C
Memory	EPC:	96Bits	96Bits	128(96)Bits	96Bits
	User:	OBits	OBits	32(64)Bits	32Bits
	TID:	48Bits	48Bits	48Bits	48Bits
	Unique TID:	48Bits	48Bits	48Bits	48Bits
	Access Password:	OBits	32Bits	32Bits	32Bits
	Kill Password:	OBits	32Bits	32Bits	32Bits
IC Life	100,000 Programming cycles				
	50 years data retention				
Operating Mode	Passive				
Frequency	860 ~ 960MHz				
Standards	ISO 9001:2008				
	ISO 14001:2004				
	OHSAS 18001:2007				

Web site: www.arizonrfid.com

Copyright © 2019 Arizon RFID Technology Corporation All rights

reserved







# 香港商永道無線射頻標籤有限公司台灣分公司

Arizon RFID Technology(Hong Kong)Co.,Ltd.,Taiwan Branch.

# Frequency Sweep






Test power: 4W EIRP


For countries that allow 2W ERP, please reduce the result by 11%

## **Radiation Patterns**

Angular Sensitivity (dBm); Power step 0.1dB; Angle step 10°



Angular Sensitivity
)Relative Read Range vs.Orientation(



Angular Sensitivity
Inlay is rotated in the x,y axis, fixed in z axis
)Tag shown at 0° with respect to face of antenna(

# **Usage Method**







Water

Arizon RFID Testing Center:

RFID UHF Band: 800-1000MHz; Shielding effectiveness: > 100 dB; Background noise: < -75 dB Compatible to the following international standard:

EPC Global Class1 Gen2; ISO 18000-6C; GS1 TIPP (Tagged Item Performance Protocol )